

### PHOENIX MOTOR GASOLINE (MOGAS) E10 EURO-4

#### 1. Product Name and Company Details

Company Name: Phoenix Petroleum Philippines Incorporated

Head Office: Phoenix Bulk Depot, Lanang, Davao City, 8000

Product Name: MOGAS E10 EURO-4

Trade Name: REGULAR E10 EURO-4

PREMIUM E10 EURO-4 PREMIUM PLUS E10 EURO-4 PREMIUM 91 E10 EURO-4

Chemical Family: Petroleum Hydrocarbon

**Product Classification:** Petroleum Distillate with Performance Additives

**Emergency Number:** +63 (82) 235 8888, +63 (82) 233 0168

**E-mail:** info@phoenixfules.ph

### 2. Composition / Information on Ingredients

Substance: The product is consist of aliphatic, alicyclic, and aromatics

hydrocarbons. It composed of distillate and residual fractions

blended to achieve the prescribed viscosity ranges. In general this product is combustible, may contain

carcinogenic components and most likely contain trace

amount of hydrogen sulfide.

Aromatics, %volume	0-35%
Benzene, %volume	0-2%
Ethanol, %volume	0-10%

#### 3. Hazards Identification

Classification of the substance According to Regulation (EC) No. 1272/2008 (CLP)

Flam. Liq. 1; H224 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Muta. 1B; H340 Carc. 1B; H350 Repr. 2; H361fd

Aquatic Chronic 2; H411

According to Directive 67/548/EEC & Directive 1999/45/EC

F+; R12

Carc. Cat. 2; R40 Muta. Cat. 2; R46 Repr. Cat. 3; R63 – R63

Xn; R65 Xi; R38 N; R51/53

Label elements According to Regulation (EC) No. 1272/2008 (CLP)

Hazard pictogram(s):



DAVAO OFFICE: Phoenix Bulk Depot, Lanang, Davao City, Philippines, 8000

MANILA OFFICE: 25<sup>th</sup> Floor

25<sup>th</sup> Floor, Fort Legend Towers, 3<sup>rd</sup> Avenue corner 31<sup>st</sup> Street, Bonifacio Global City Taguig City, Philippines 1634 www.phoenixfuels.ph

## PHOENIX MOTOR GASOLINE (MOGAS) E10 EURO-4



Signal word(s): Danger

Hazard Statement(s): H224: Extreme Flammable liquid and vapor.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H340: May cause genetic defects.

H350: May cause cancer.

H361fd: Suspected of damaging fertility. Suspected of damaging the

unborn child.

H411: Toxic to aquatic life with long lasting effects.

Precautionary statement(s): P201: Obtain special instructions before use.

P210: Keep away from heat, sparks, open flame, hot surfaces - No

P280: Wear protective gloves/protective clothing/eye protection/face

protection.

P301 + P310: IF SWALLOWED: Immediately call a POISON

CENTRE or doctor/physician.

P403 + P233: Store in a well-ventilated place. Keep container tightly

closed.

P501: Dispose of contents/container to: Disposal should be in

accordance with local, state or national legislation.

Label elements

Hazard pictogram(s):

According to Directive 67/548/EEC & Directive 1999/45/EC







Extremely flammable. Dangerous for the environment. Hazard symbol:

R12: Extremely flammable. Risk phrases:

R38: Irritating to skin. R45: May cause cancer.

R46: May cause heritable genetic damage.

R51/53: Toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment. R62: Possible risk of impaired fertility.

R63: Possible risk of harm to the unborn child. R65: Harmful: may cause lung damage if swallowed. R67: Vapors may cause drowsiness and dizziness.

Safety phrases:

S2: Keep out of the reach of children. S23: Do not breathe fumes/vapor. S24: Avoid contact with skin.

S29: Do not empty into drains.

S36/37: Wear suitable protective clothing and gloves.

S45: In case of accident or if you feel unwell, seek medical advice

immediately (show the label where possible).

S51: Use only in well-ventilated areas.

S53: Avoid exposure - obtain special instructions before use.

S61: Avoid release to the environment. Refer to special

instructions/Safety Data Sheets.

S62: If swallowed, do not induce vomiting: seek medical advice

immediately and show this container or label.

Other hazards: Vapor may create explosive atmosphere. The vapor is heavier than

air; beware of pits and confined spaces. May cause irritation to eyes

and air passages.

DAVAO OFFICE:

Phoenix Bulk Depot, Lanang, Davao City, Philippines, 8000

MANILA OFFICE:

25<sup>th</sup> Floor, Fort Legend Towers, 3<sup>rd</sup> Avenue corner 31 <sup>st</sup> Street, Bonifacio Global City Taguig City, Philippines 1634

www.phoenixfuels.ph







#### 4. First Aid Measures

Description of first aid

measures Inhalation:

Remove patient from exposure, keep warm and at rest. If symptoms

persist, obtain medical attention.

Skin contact: Remove contaminated clothing immediately and drench affected

skin with plenty of water, then wash with soap and water. If symptoms persist, obtain medical attention. Contaminated clothing

should be thoroughly cleaned.

Eye contact: If substance has got into the eyes, immediately wash out with plenty

of water for at least 15 minutes. If symptoms persist, obtain medical

attention.

Ingestion: Obtain immediate medical attention. Do not induce vomiting.

Provided the patient is conscious, wash out mouth with water and

give 200-300 ml (half a pint) of water to drink.

Most important symptoms and effects, both acute and delayed

Aspiration hazard. Irritating to skin. May cause irritation to eyes and

air passages.

Indication of the immediate medical attention and special treatment needed

If breathing is labored, oxygen should be administered by qualified personnel. In case of accident or if you feel unwell, seek medical

advice immediately (show the label where possible).

#### 5. Fire-Fighting Measures

**Extinguishing media** 

Suitable extinguishing

media:

Foam, CO2 or dry powder. For large fire use: Water.

Unsuitable extinguishing media:

Special hazards arising from the

Do not use water jet.

Vapor may create explosive atmosphere. The vapor is heavier than air; beware of pits and confined spaces.

Advice for fire fighters

substance

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep fire exposed containers cool

by spraying with water.

### 6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Eliminate sources of ignition. Vapor may create explosive atmosphere. The vapor is heavier than air; beware of pits and confined spaces. Ensure adequate ventilation. Use nonsparking hand tools and explosion proof electrical equipment. Take

precautionary measures against static discharges.

Avoid inhalation of vapors. Avoid contact with skin and eyes. Wear suitable protective clothing and gloves. (See Section: 7).

Contaminated clothing should be thoroughly cleaned.

**Environmental precautions** Do not allow to enter drains, sewers or watercourses. Spillages or

uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.





Methods and materials for containment and clean up

Adsorb spillages onto sand, earth or any suitable adsorbent material. Sweep up carefully with non-sparking tools. Transfer to a container for disposal. Wash spill area with soapy water. Contaminated adsorbent must be removed in sealed, plastic lined drums and disposed of via an authorized waste disposal contractor.

#### 7. Handling and Storage

#### Precautions for safe handling

Eliminate sources of ignition. Vapor may create explosive atmosphere. The vapor is heavier than air; beware of pits and confined spaces. Provide adequate ventilation, including appropriate local extraction, to ensure that the occupational exposure limit is not exceeded. Use non-sparking hand tools and explosion proof electrical equipment. Take precautionary measures against static discharges.

Hydrocarbon liquids including this product can act as a non-conductive flammable liquid (or static accumulators), and may form ignitable vapor-air mixtures in storage tanks or other containers. Precautions to prevent static-imitated fire or explosion during transfer, storage or handling, include but are not limited to these examples:

- (1) Ground and bond containers during product transfers. Grounding and bonding may not be adequate protection to prevent ignition or explosion of hydrocarbon liquids and vapors that are static accumulators.
- (2) Special slow load procedures for "switch loading" must be followed to avoid the static ignition hazard that can exist when higher flash point material (such as fuel oil or diesel) is loaded into tanks previously containing low flash point products (such gasoline or naphtha).
- (3) Storage tank level floats must be effectively bonded.

Avoid inhalation of vapors. Avoid contact with skin and eyes.

Do not eat, drink or smoke at the work place. Wash hands and exposed skin after use. Contaminated clothing should be thoroughly cleaned.

Wear suitable protective clothing and gloves. (See Section: 7).

# Conditions for safe storage, including any incompatibilities

Keep away from heat and sources of ignition. Keep from direct sunlight. Keep only in the original container in a cool, well ventilated place. Keep/store away from: Oxidizing agents.

Reports suggest that government-mandated ethanol, if present, may not be compatible with fiberglass gasoline tanks. Ethanol may dissolve fiberglass resin, causing engine damage and possibly allow leakage of explosive gasoline.

#### Specific end use(s)

### 8. Exposure Controls/Personal Protection

**Control parameters** 

No occupational exposure limit assigned.

Exposure controls Appropriate engineering controls Provide adequate ventilation, including appropriate local Extraction, to ensure that the occupational exposure limit is not exceeded.





### **Personal protection**

Eye/face protection



Goggles giving complete protection to eyes. (EN 166)

Skin protection



Protective gloves. (EN 374)

Respiratory protection



In case of insufficient ventilation, wear suitable respiratory equipment. (BS EN 14387:2004+A1)

Apron or other light protective clothing, boots and plastic or Other:

rubber gloves.

**Environmental exposure controls** 

Avoid release to the environment.

#### 9. Physical and Chemical Properties

Information on basic physical and

chemical properties

Physical State at 20°C Liquid Water Solubility Insoluble Density at 15°C, kg/L 0.7403

Characteristic Petroleum product

www.phoenixfuels.ph

Vapor Pressure at 37.8°C, kPa 54.5

Viscosity at 50°C, mm<sup>2</sup>/s Not Applicable Pour Point,°C Not Applicable

#### 10. Stability and Reactivity

Reacts with strong oxidizing agents. Reactivity

Stable under normal conditions. **Chemical stability** 

No information available. Possibility of

hazardous reactions

Keep away from heat, sources of ignition and direct sunlight. Conditions to avoid

Incompatible Oxidizing agents.

materials

**Hazardous** May give off toxic fumes in a fire. Carbon monoxide, Carbon dioxide

and various hydrocarbons. decomposition

byproduct(s) DAVAO OFFICE:

Phoenix Bulk Depot, Lanang, Davao City, Philippines, 8000  $25^{\rm m}$  Floor, Fort Legend Towers,  $3^{\rm rd}$  Avenue corner 31  $^{\rm st}$  Street, Bonifacio Global City Taguig City, Philippines 1634 MANILA OFFICE:



### PHOENIX MOTOR GASOLINE (MOGAS) E10 EURO-4

#### 11. Toxicological Information

Information on toxicological effects

**Acute Toxicity:** 

LD<sub>50</sub> (oral/rat): 7600 mg/kg (API, 1980a, b) Ingestion

Inhalation LC<sub>50</sub> (inhalation/rat): 4.1 mg/l/4 h (ARCO, 1988)

Skin contact LD<sub>50</sub> (dermal/rabbit): 4300 mg/kg (API, 1980a,b)

Eve contact No information available.

Skin irritation: Irritating to skin.

Serious eye damage: May cause eye irritation.

Respiratory or skin Negative.

sensitization:

Mutagenicity: There is no evidence of mutagenic potential.

Carcinogenicity: No evidence of carcinogenicity.

Reproductive Negative.

toxicity:

Negative.

STOT-single

exposure: May cause damage to organs through prolonged

exposure. **STOT-repeated** 

exposure:

Risk of aspiration. Aspiration of liquid may caus Aspiration hazard:

oedema.

12. Ecological Information

LC<sub>50</sub>: (Rainbow trout): 1-10 mg/l/96h **Toxicity** EC<sub>50</sub> (Daphnia magna): 1-10 mg/l/48h

NOEL: 0.083 mg/l/14 days

WGK: Not established.

Persistence and Persistent. Not readily biodegradable. Part of the c degradability

poorly biodegradable.

**Bioaccumulative** The product has potential for bioaccumulation. Log Kow potential

Mobility in soil

The product has low mobility in soil.

Results of PBT and vPvB Half-life: 1.2-2.7 days. assessment

13. Disposal Considerations

Waste treatment methods Do not empty into drains; dispose of this material

and its container in a safe way. To be disposed of as hazardous waste. Disposal should be in

accordance with local, state or national legislation.



### PHOENIX MOTOR GASOLINE (MOGAS) E10 EURO-4

### 14. Transport Information

1203 **UN Number** 

**Proper shipping** 

Petrol name

**Transport hazard** 

class(es)

**Environmental** Ш

hazard(s)

Special precautions Vapor may create explosive atmosphere. The vapor is for user

3

heavier than air; beware of pits and confined spaces.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code:

Not applicable.

#### 15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

When used for its intended purposes, this material is not

classified as hazardous.

#### 16. Other Information

Not applicable

However, no representation, warranty or guarantee is more as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.

REV.2 effective February 2018