SAFETY DATA SHEET PHOENIX ZDO 30 1. Product Name and Company Details



Company Name:	Phoenix Petroleum Philippines Incorporated
Head Office:	Phoenix Bulk Depot, Lanang, Davao City, 8000
Taguig Office:	25 th Flr. Fort Legend Towers 3 rd Ave. cor. 31 st St. Fort Bonifacio Global City, Taguig City, 1634, Philippines
Product Name:	ZDO 30
Chemical Family:	Petroleum Hydrocarbon
Product Classification:	Diesel Engine Oil
Product Description:	API CC/SC SAE 30
Emergency Number:	+63 (2) 4034013, +63 (2) 4034025
Taguig Office: Product Name: Chemical Family: Product Classification: Product Description:	25 th Flr. Fort Legend Towers 3 rd Ave. cor. 31 st St. Fort Bonifacio Global City, Taguig City, 1634, Philippines ZDO 30 Petroleum Hydrocarbon Diesel Engine Oil API CC/SC SAE 30

2. Composition / Information on Ingredients

Highly refined mineral base oils-about 95%, OIL additives 5-8%

3. Hazard Identification

Warning Statement:	Avoid frequent skin contact to Used Motor Oil. Wash skin with soap and water to prevent skin irritation that may result to redness and dryness of the affected area.
Eyes Contact:	Causes minor eye irritation characterized by tearing or burning sensation
Oral / Ingestion:	If swallowed may cause abdominal discomfort
Inhalation:	Breathing of mist or vapor may result to difficulty of breathing
Skin Contact:	Prolonged skin contact may result to redness or drying of the skin
4. First Aid Measures	
Eyes Contact:	Immediately flush eyes with large amount of water for at least 15 minutes.
Skin Contact:	Immediately flush with large amount of water, use soap if available. Remove contaminated clothing, including shoes, after flushing has begun. If irritation persists, get medical attention.
Inhalation:	Generally not an inhalation hazard. Using respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention.
Ingestion:	Do not induce vomiting. If individual is conscious, give water to dilute stomach contents. Keep warm and quiet. Get prompt medical attention.
5. Fire Fighting Measures	
Flash Point:	220°C
Fire Point:	250⁰C
Flammability Limits:	>220°C
DAVAO OFFICE: Phoenix Bulk Depot, Lanang, Davao City, Philippines, 8000	MANILA OFFICE: 25 th Floor, Fort Legend Towers, www.phoenixfuels.ph 3 rd Avenue corner 31 st Street, Bonifacio Global City Taguig City, Philippines 1634

SAFETY DATA SHEET PHOENIX ZDO 30



Extinguishing Media:	CO ₂ , dry chemical, or foam		
Special Firefighting:	Recommend wearing self-contained breathing apparatus.		
Procedures:	Do not use a water jet, as this may spread the fire. In the absence of suitable extinguishers, sand or earth may be used to smother small fires.		
6. Accidental Release Measu	ires		
Land Spill:	Contain spilled liquid with sand or earth. Recover by pumping or with a suitable absorbent. If liquid is too viscous for pumping, scrape up with shovel or pails and place in suitable containers for recycle or disposal. Consult an expert on disposal or recovered material and ensure conformity to local disposal regulations.		
Water Spill:	Consult local environmental authorities.		
7. Handling and Storage			
Max. Storage temperature, (°C):	40°C		
Max. Transport temperature, (°C	: 40°C		
Handling procedures:	Keep containers closed when not in use. Handle containers with care. Open slowly in order to control possible pressure release. Do not handle, store or open near an open flame.		
Storage procedures:	No special storage precautions required.		
8. Special Protection Information	8. Special Protection Information		
Ventilation Requirements:	Normal ventilation		
Respiratory Protection:	Avoid inhalation		
Eye Protection:	Safety Goggles		
Protective Gloves:	Rubber or cloth		
9. Physical and Chemical Pro	operties		
Typical physical and chemical properties are given below. Consult the supplier in section 1 for additional data.			
i ypical physical and chemical propertie	י איזיט איזיע איזיט איזיע איז		

Physical State at 20ºC	Liquid
Water Solubility	Insoluble
Density at 15⁰C, kg/L	886
Appearance/Odor	Amber colored liquid
Viscosity at 40ºC, cSt.	100 to 120
Pour Point, ºC	-6
Melting Point, ºC	Not applicable
Flash Point (COC), ºC	220

SAFETY DATA SHEET PHOENIX ZDO 30



10. Stability and Reactivity

Stability:	Material is stable under normal conditions.
Conditions to avoid:	Excessive heat
Materials to avoid:	Strong oxidizers such as chlorates, nitrates, peroxides, etc.
Hazardous decomposition product:	Material does not decompose at ambient temperature.

11. Toxicological Information

No specific toxicological data on this product is available.

12. Ecological Information

May present environmental risks common to oil spills

13. Disposal Consideration

Disposal must be in accordance with current applicable laws and regulations. Contact local authorities

for proper environmental disposal of this material.

14. Transport Regualtion	
DOT:	Not regulated
15. Regulatory Information	
OSHA Hazard Communication Standard:	When used for its intended purposes, this material is not classified as hazardous.
Chemical Name:	N/A
16. Other Information	

No specific notes on this product

However, no representation, warranty or guarantee is more as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability

and completeness of such information for his own particular use.

REV.3 effective April, 2018