



# PNX CYCLOMAX

SAE 10W-40 | API SL/JASO MA2/MA

### Description

**PNX CYCLOMAX 10W-40 API SL/JASO MA2/MA** is a 100% synthetic four-stroke motorcycle oil formulated with **HEAT GUARD** additives that resists engine overheating at high speed driving for a more cooler and comfortable ride. It also provides excellent protection against wear even in stressful stop and go driving conditions.

### Performance Specifications:

- Exceeds JASO MA2/MA ( T903:2016)
- API SL

### Product Benefits:

- Keeps engine cool
- Excellent wear protection
- Longer Oil Change Interval
- Extends Engine Life
- Enhance Power and Acceleration

### Recommended Application:

- Meets OEM specification and recommended to be used in all types of motorcycles (Japanese and European) that require API SL/JASO MA2/MA and below performance level
- PNX Cyclomax with Heat Guard formulation exceeds the JASO MA2 performance.
- Suitable to be used for daily rides with stop/go road, and all weather conditions

### Typical Properties:

Parameters	Unit	Method	SAE 10W-40
Appearance		Visual	C&B
Color		ASTM D1500	L2.0
Kinematic Viscosity @ 40°C	cSt	D445	96.45
Kinematic Viscosity @ 100°C	cSt	D445	14.69
Viscosity Index		D2270	159
Density @ 15°C	Kg/L	D1298/D4052	0.856
Flash Point	°C	D92	238
Total Base Number	Mg KOH/g	D2896	5.9