



PNX CYCLOMAX

SAE 10W-40 API SL/JASO MB

Description

PNX CYCLOMAX SAE 10W-40 API SL/JASO MB is a 100% synthetic four stroke oil formulated with **HEAT GUARD** additive for MATIC motorcycles. The formulation delivers continuous protection especially to resist engine overheating and wear especially during stop & go driving situations for a cooler ride.

Performance Specifications:

- JASO MB (T903:2016)
- API SL

Product Benefits:

- Keeps engine cool
- Excellent wear protection
- Longer Oil Change Interval
- Extends Engine Life

Recommended Application:

- Meets OEM specification and recommended to be used in all type of MATIC motorcycles (Japanese and European) that require API SL/JASO MB and below performance level
- Suitable to be used for daily rides with stop/go road, and all weather conditions

Typical Properties:

Parameters	Unit	Method	SAE 10W-40
Appearance		Visual	C&B
Color		ASTM D1500	L3.0
Kinematic Viscosity @ 40°C	cSt	D445	96.44
Kinematic Viscosity @ 100°C	cSt	D445	14.72
Viscosity Index		D2270	159
Density @ 15°C	Kg/L	D1298/D4052	0.856
Flash Point	°C	D92	236
Total Base Number	Mg KOH/g	D2896	6.0