



# PNX CYCLOMAX

SAE 20W-40 | API SL/JASO MA2/MA

## Description

**PNX CYCLOMAX SAE 20W-40 API SL/JASO MA2/MA** is a premium four stroke motorcycle oil formulated with **HEAT GUARD** additives that resists engine overheating for a cooler and comfortable ride. It also provides excellent protection against wear even in stressful stop and go driving conditions.

## Performance Specifications:

- Exceeds JASO MA2/MA ( T903:2016)
- API SL

## Product Benefits:

- Keeps engine cool
- Excellent wear protection
- Longer Oil Change Interval
- Extends Engine Life
- Enhance Power and Acceleration

## Recommended Application:

- Meets OEM specification and recommended to be used in all types of motorcycles (Japanese and European) that require API SL/JASO MA2/MA and below performance level
- PNX Cyclomax with Heat Guard formulation exceeds the JASO MA2 performance.
- Suitable to be used for daily rides with stop/go road, and all weather conditions

## Typical Properties:

Parameters	Unit	Method	SAE 20W-40
Appearance		Visual	C&B
Color		ASTM D1500	L2.0
Kinematic Viscosity @ 40°C	cSt	D445	128.5
Kinematic Viscosity @ 100°C	cSt	D445	14.74
Viscosity Index		D2270	116
Density @ 15°C	Kg/L	D1298/D4052	0.879
Flash Point	°C	D92	244
Total Base Number	Mg KOH/g	D2896	5.9