



# PNX CYCLOMAX

SAE 20W-40 API SL/JASO MB

## Description

**PNX CYCLOMAX SAE 20W-40 API SL/JASO MB** is a premium mineral four stroke motorcycle oil formulated with **HEAT GUARD** additives for MATIC motorcycles. The formulation delivers continuous protection especially to resist engine overheating and wear especially during stop & go driving situations for a cooler ride.

## Performance Specifications:

- JASO MB ( T903:2016)
- API SL

## Product Benefits:

- Keeps engine cool
- Excellent wear protection
- Longer Oil Change Interval
- Extends Engine Life

## Recommended Application:

- Meets OEM specification and recommended to be used in all type of MATIC motorcycles (Japanese and European) that require API SL/JASO MB and below performance level
- Suitable to be used for daily rides with stop/go road, and all weather conditions

## Typical Properties:

Parameters	Unit	Method	SAE 20W-40
Appearance		Visual	C&B
Color		ASTM D1500	L2.5
Kinematic Viscosity @ 40°C	cSt	D445	126.1
Kinematic Viscosity @ 100°C	cSt	D445	14.63
Viscosity Index		D2270	117
Density @ 15°C	Kg/L	D1298/D4052	0.880
Flash Point	°C	D92	228
Total Base Number	Mg KOH/g	D2896	6.0